

Ease of use and reliability at a competitive price

The new BU500 burnisher is a 1500rpm belt driven machine. Improved ergonomic features enables ease of use and transportation, such as the NEW ergonomic handle, trip fuse, built-in padholder, 15m cable and robust construction.

This machine is at the edge of safety with its dead mans switch, safety button & high visibility cable, resulting in this being the perfect machine for hospital cleaning. A metal frame, big wheels, bumpers and gloss paint, all merged together in a modern design gives evidence to the robustness, durability and easy cleaning of the machine.

- Price competitive: extremely competitive on pricing against major competitors
- Nilfisk Brand: Enables cost savings and complexity reduction
- Improved features: cable hook, big wheels, safety, easy cable replacement and ergonomic handle



Picture shown may not represent model quoted

• Standard equipment

Model	BU500 UK
Ref. no.	56380064

PRODUCT FEATURES

Spray cleaning	•
Cable holder	•
Uk model	•
Ergonomic handle	•
Folding handle	•
High visibility cable	•
Easy cable change	•
Belt drive	•
Burnishing	•




Technical specifications	BU500 UK
Plug type	UK
Voltage (V)	230
Frequency (Hz)	50
Protection class / IP protection	IPX0
Rated power (W)	1100
Sound pressure level at 1.5 m (dB(A) ISO 3744)	>70
Handle vibration level (m/s ²)	<2.5



Ease of use and reliability at a competitive price

Technical specifications	BU500 UK
Cable length (m)	15
Brush/pad diameter (mm)	510
Brush/pad pressure (g/cm ²)	10
Brush/pad speed (RPM)	1500
Brush torque (nm)	12
Length x width x height (mm)	824x566x1261
Height motorhousing (mm)	na
Height w/handle vertical (mm)	1261
Weight (kg)	41

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories		Ref. no.	Min. required	BU500 UK
Special Pad				
	PAD 20 508MM ECO BRILLIANCE GREEN 2PCS	10002351	1	○
Pad 20" / 508 mm				
	PAD 20 508MM ORANGE GREEN 5 PCS	L00305600	1	○
	PAD 20 508MM ORANGE WHITE 5 PCS	L00190840	1	○

